# Brass SAE 45° Flare Fittings

#### Applications:

· for use with copper, brass, aluminum and welded steel hydraulic tubing that can be flared

#### Features:

- · economical fitting
- · resists mechanical pullout
- · easy to disassemble and may be reassembled repeatedly, for a leak-proof connection
- manufactured from CA 360, CA 345, or CA377 brass
- for use with hard-to-hold liquids and gases
- Listed with Underwriter's Laboratories for flammable liquid, marine, refrigeration and gas applications. Meets functional requirements of SAE J512 and J513, ASA and MS (Military Standards).
- temperature range: -65°F to 250°F (-54°C to 121°C)

## **Working Pressure Ranges:**

Temperature and type of tubing used are important factors, the following table is a general guide for proper selection. The PSI rating given is based on a temperature of 73°F (22°C) using copper tubing.

PSI	Tube OD	Tube Wall
1400	1/4"	.030
1000	3/8"	.032
750	1/2"	.032
650	5/8"	.035
550	3/4"	.035

#### **Assembly Instructions:**

- 1. Cut tubing squarely and clean tube end thoroughly to remove burrs.
- 2. Place nut onto tube. Place threaded end of nut toward end of tube.
- 3. Flare tube end with flaring tool to provide 45° flare (flare tools are available, please contact Dixon® for pricing and availability).
- 4. Clamp tube flare between nut and nose of fitting body by screwing nut on finger-tight. Tighten with a wrench an additional 1/4 turn for a metal-to-metal seal.

## **Male Connectors**

### Feature:

reference SAE 010102

Tube Size	Pipe Size	Straight Thread	Hex	<i>Brass</i> Part #
1/4"	1/4"	7/16"-20	9/16"	48F-4-4
	3/8"	7/16"-20	11/16"	48F-4-6
	1/2"	7/16"-20	7/8"	48F-4-8
3/8"	1/8"	5/8"-18	5/8"	48F-6-2
	1/4"	5/8"-18	5/8"	48F-6-4
	3/8"	5/8"-18	11/16"	48F-6-6
	1/2"	5/8"-18	7/8"	48F-6-8
1/2"	1/4"	3/4"-16	3/4"	48F-8-4
	3/8"	3/4"-16	3/4"	48F-8-6
	1/2"	3/4"-16	7/8"	48F-8-8
5/8"	3/8"	7/8"-14	7/8"	48F-10-6
3/4"	3/4"	1-1/16"-14	1-1/16"	48F-12-12





#### Feature:

reference SAE 010103

releience SAL 010103							
	Tube Size	Pipe Size	Straight Thread	Hex	<i>Brass</i> Part #		
	1/4"	1/4"	7/16"-20	11/16"	46F-4-4		
3/8"	1/4"	5/8"-18	11/16"	46F-6-4			
	3/8"	5/8"-18	13/16"	46F-6-6			
	1/2"	5/8"-18	1"	46F-6-8			
1/2"	1/4"	3/4"-16	3/4"	46F-8-4			
	3/8"	3/4"-16	13/16"	46F-8-6			
	5/8"	3/8"	7/8"-14	7/8"	46F-10-6		



**Female Connectors**