

## Specialty Caps

## Plugs with Cable - Rocker Lug

## Feature:

- -NC: no cable option available

Size	<i>Extruded Hardcoated Aluminum</i>	
	NST (NH) Part #	NPSH Part #
1½"	<b>PLUG150F-C</b>	<b>PLUG150S-C</b>
2½"	<b>PLUG250F-C</b>	<b>PLUG250S-C</b>
3"	<b>PLUG300F-C</b>	<b>PLUG300S-C</b>
4"	<b>PLUG400F-C</b>	---
4½"	<b>PLUG450F-C</b>	---
5"	<b>PLUG500F-C</b>	---
6"	<b>PLUG600F-C</b>	---



## Cap Test Gauges

## Application:

Used for testing hose or static pressure on hydrants or trucks

## Features:

- rocker lug swivel
- petcock to release pressure
- supplied with a 0-300 PSI glycerine 3½" diameter gauge

NST (NH) Thread	<i>Hardcoated Aluminum</i> Part #
1½"	<b>AFC150F-TGWP</b>
2½"	<b>AFC250F-TGWP</b>



## FDC Plugs

## Features:

- fits standard 2½" NST (NH) female swivel
- withstands wide range of temperatures from -4°F to 200°F (-20°C to 93°C)
- 1½" pentagonal nut with weep hole to allow for drainage
- removed from FDC with adjustable hydrant wrench

Size	Thread	<i>Polycarbonate</i> Part #
1½"	NST (NH)	<b>PP150F</b>
2½"	NST (NH)	<b>PP250F</b>
2½"	NYFD	<b>PP250NYFD</b>



## Adjust-A-Plug

## Features:

- molded red polycarbonate protective plug for swivel connections up to 2½"
- two adjustable metal plates installed in the back of the plug can be mated with your local thread
- plug can be easily removed with a fire department spanner wrench

<i>Polycarbonate</i> Part #
<b>PAP250</b>



front



back