

Grooved Angle Valves

Application:

· commercial fire protection

Features:

- made in the USA
- · easy for contractor to install
- groove inlet
- · Buna-N gasket
- working pressure: 300 PSI at 70°F (21°C)
- · UL listed, FM approved, ULC approved

| Description | Cast Brass Part # |
|-----------------|----------------------|
| groove x male | AVG250F |
| groove x groove | AVG250G |
| groove x female | AVGF250 |



500# Angle Hose Valves

Applications:

 fire department, gravity and pressure tank connections, test connections, and public water supplies to sprinkler and standpipe systems where it is necessary to access the system for a fire hose connection

Features:

- designed and approved to manage 500 PSI pressures in piping systems
- red handwheel
- FM approved
- New York City Board of Standards and Appeals, approval # MEA 54-07-E
- maximum operating pressure: 500 PSI at 70°F (21°C)



Female x Male

| Inlet | Outlet | Cast Brass |
|------------|--------------|-------------|
| Female NPT | Male Thread | Part # |
| 2½" | 2½" NST (NH) | AV5-250F |
| 2½" | 2½" NYFD | AV5-250NYFD |



Female x Female

| Inlet | Outlet | <i>Cast Brass</i> |
|------------|------------|-------------------|
| Female NPT | Female NPT | Part # |
| 2½" | 2½" | AVF5-250 |