

## Elbows

### Angle and Suction

**Features:**

- for use on pump discharge valves, or suction inlets to minimize hose kinking
- rocker lug swivel
- satin brass finish
- -C polished chrome plated

| Male NST (NH) | Female NST (NH) | Angle | Brass Part #       | Price/E         |
|---------------|-----------------|-------|--------------------|-----------------|
| 2½"           | 2½"             | 30°   | <b>RSE30250F-C</b> | <b>\$358.10</b> |
| 2½"           | 2½"             | 45°   | <b>RSE45250F</b>   | <b>209.10</b>   |
| 2½"           | 2½"             | 45°   | <b>RSE45250F-C</b> | <b>298.00</b>   |
| 2½"           | 2½"             | 90°   | <b>RSE90250F</b>   | <b>216.00</b>   |
| 2½"           | 2½"             | 90°   | <b>RSE90250F-C</b> | <b>242.00</b>   |



30° elbow



45° elbow

### Continuous Swivel

**Features:**

- allows hose to swing when connected
- full waterway reduces friction loss
- short style radius is 2½" measured from the center of the waterway to the end of the discharge thread

| Female NPT | Male Thread  | Length | Cast Brass Part # | Price/E         |
|------------|--------------|--------|-------------------|-----------------|
| 1½"        | 1½" NST (NH) | 2½"    | <b>CSES150F</b>   | <b>\$180.00</b> |
| 2"         | 1½" NST (NH) | 2½"    | <b>CSES2015F</b>  | <b>180.00</b>   |
| 1½"        | 1½" NPT      | 2½"    | <b>CSES150T</b>   | <b>180.00</b>   |



## Dixon™ Adapters

### N54 - Angle and Suction Elbows

**Features:**

- ideal for fire apparatus with front suction connections
- anodized, powder coated aluminum, extruded
- anodized female swivel connections

| Angle | Male NST (NH) | Female NST (NH) Swivel | Aluminum Part #     | Price/E         |
|-------|---------------|------------------------|---------------------|-----------------|
| 30°   | 2½"           | 2½"                    | <b>N5430-25F25F</b> | <b>\$318.70</b> |
| 45°   | 2½"           | 2½"                    | <b>N5445-25F25F</b> | <b>262.50</b>   |
| 60°   | 2½"           | 2½"                    | <b>N5460-25F25F</b> | <b>330.90</b>   |
| 90°   | 2½"           | 2½"                    | <b>N5490-25F25F</b> | <b>332.80</b>   |



90° elbow

P