Polyethylene Strainers

NDT Sizo	Black Polyethylene		
NPT Size	Part #	Price/E	
1½"	TSS20	\$12.70	
2"	TSS25	12.70	
3"	TSS35	27.10	



LIQUIfit™ Fittings

Application:

Suitable for water, potable liquids and neutral gas applications: including water filtration, water coolers, coffee machines and beverage dispensers.

Features:

- EPDM seal secures connection with larger surface area than standard O-rings
- engineered polymer allows superior mechanical strength and chemical resistance
- full stainless gripping ring eliminates the need for locking
- release button protects and supports tubing
- FDA compliant
- meets California and Vermont <0.25% lead requirements
- NSF-51 listed for contact with food
- NSF-61 list C-Hot rated
- in compliance with the following standards:





Specifications:

- working pressure:
 - 1/4" 230 PSI from 35°F to 100°F 150 PSI at 150°F 60 PSI at 200°F
 - 190 PSI from 35°F to 100°F 100 PSI at 150°F **60 PSI at 200°F**
 - 160 PSI from 35°F to 100°F 100 PSI at 150°F 60 PSI at 200°F
- maximum torque values for NPTF threads:

1/4" and 1/4" 1.0 ft. lbs. / 1.5Nm 3/8" and 1/2" 2.2 ft. lbs. / 3.0Nm

Male Connectors



tube to male NPTF

Tube OD	Male NPTF	<i>Nylon</i> Part #	Price/E	Pkg Qty
1/4"	1/8"	65055611WP2	\$2.50	10
1/4"	1/4"	65055614WP2	2.90	10
3/8"	1/4"	65056014WP2	4.25	10
3/8"	3/8"	65056018WP2	4.85	10
1/2"	3/8"	65056218WP2	6.70	5
1/2"	1/2"	65056222WP2	7.20	5





tube to female UNS

Tube OD	Female UNS	<i>Nylon</i> Part #	Price/E	Pkg Qty
1/4"	7/16-24	632556133WP2	\$4.90	10
3/8"	7/16-24	632560133WP2	5.50	10

Female Connectors



tube to female NPTF

Tube OD	Female NPTF	<i>Nylon</i> Part #	Price/E	Pkg Qty
1/4"	1/4"	63155614WP2	\$6.00	10
3/8"	3/8"	63156018WP2	6.90	10

Fixed Flbows



tube to male NPTF

Tube OD	Male NPTF	<i>Nylon</i> Part #	Price/E	Pkg Qty
1/4"	1/8"	65795611WP2	\$3.90	10
1/4"	1/4"	65795614WP2	4.40	10
1/4"	3/8"	65795618WP2	5.20	10
3/8"	1/4"	65796014WP2	5.75	10
3/8"	3/8"	65796018WP2	5.90	10