

Spiral Hose and Cable Protection

Application:

- used in mining, quarrying, forestry, offshore industries and most hydraulic hose applications

Features:

- crush and high abrasion resistance
- chemical and UV ray resistant
- self-lubricating to reduce hose wear
- easy to install on-site
- smooth radius on all edges
- can be used on single or multiple hose bundles
- spiral guard ID is equal to the guard at rest
- sold in coil lengths only



Standard



Flame Retardant

Flame Retardant Product

Features:

- approved by MSHA #1C-264/0
- tested to: AS 2600, AS1180.10B, AS 1180.13A
- flame retardant, self extinguishing, anti static
- temperature range: **-148°F to 262°F**, (-100°C to 100°C)
- color: black

Nominal ID	Coil Length	OD Range (inches)	Part #	Price/E
0.45"	66'	.47" to .86"	FRSGX16	\$229.00
0.55"	66'	.62" to 1.06"	FRSGX20	296.00
0.80"	66'	.86" to 1.37"	FRSGX25	372.00
1.00"	66'	1.06" to 1.69"	FRSGX32	659.95
1.26"	66'	1.30" to 2.17"	FRSGX40	848.00
1.50"	66'	1.65" to 2.52"	FRSGX50	1184.75
2.00"	66'	2.05" to 2.95"	FRSGX63	1540.00
2.40"	66'	2.56" to 3.80"	FRSGX75	2012.00
2.83"	66'	3.15" to 4.30"	FRSGX90	2362.00
3.43"	33'	3.80" to 4.90"	FRSGX110	1563.00

Standard Product

Features:

- not flame retardant
- temperature range: **-40°F to 248°F**, (-50°C to 90°C)

Nominal ID	Coil Length	OD Range (inches)	Part #	Price/E
0.45"	66'	.47" to .86"	NFSGX16	\$102.50
0.55"	66'	.62" to 1.06"	NFSGX20	142.90
0.80"	66'	.86" to 1.37"	NFSGX25	197.20
1.00"	66'	1.06" to 1.69"	NFSGX32	282.60
1.26"	66'	1.30" to 2.17"	NFSGX40	419.25
1.50"	66'	1.65" to 2.52"	NFSGX50	549.70
2.00"	66'	2.05" to 2.95"	NFSGX63	754.65
2.40"	66'	2.56" to 3.80"	NFSGX75	1080.70
2.83"	66'	3.15" to 4.30"	NFSGX90	1397.50
3.43"	33'	3.80" to 4.90"	NFSGX110	832.30

Fire Jacket for Hose

Application:

- used to protect hose and hose assemblies, tubing, piping, wiring and cables from high temperatures, direct flame or molten splash, helps maintain line temperature and reduce environmental overheating and overcooling

Features:

- meets Flammability requirements of UL 94 HB & UL 94 V-0
- sleeving slides easily over hose & expands to go over fittings
- resistant to hydraulic fluids and lubricating oil
- iron oxide red color
- compounded silicone rubber coating over fiberglass
- completely non-asbestos, REACH - ROHS compliant
- supplied in 50' lengths
- temperature range: **-65°F to 500°F** (-54°C to 260°C)

Nominal ID	Part #	Price/E	Nominal ID	Part #	Price/E
1/4"	0610-4	\$185.40	1 1/4"	3210-20	\$475.20
3/8"	1010-6	220.25	1 1/2"	3810-24	539.00
1/2"	1310-8	243.50	1 3/4"	4510-28	660.50
5/8"	1610-10	278.10	2"	5110-32	776.25
3/4"	1910-12	310.00	2 1/2"	6410-40	959.50
7/8"	2210-14	371.00	3"	7610-48	1393.60
1"	2510-16	394.00	4"	10210-64	1718.20



Fire Jacket Tape

Application:

used to seal the ends of fire jackets to prevent fraying and fluid wicking

Features:

- completely non-asbestos
- iron oxide red color
- temperature range: **-45°F to 380°F** (-45°C to 200°C)

Size	Length	Silicone Rubber Part #	Price/E
1"	12 yards	FTH100	\$52.50



Non Adhesive Fire Tape

Features:

- fiberglass coated silicone rubber
- fluid resistant to hydraulic fluids and lubricating oils
- should be installed in a spiral wrap utilizing 30% to 50% overlap
- iron oxide red color
- temperature range: **-65°F to 500°F**

Size	Length	Part #	Price/E
3" width	50'	4055-3	\$660.50

