

Cam & Groove Encapsulated Gaskets

Features:

- *PTFE encapsulated silicone* (TES) gaskets contain FDA approved materials
- encapsulated gasket pressure ratings are reduced to **125 PSI** for ¾" - 4" at ambient temperature **70°F (21°C)**
- *PTFE encapsulated FKM* (TEV) gaskets - maximum operating temperature **200°F (93°C)**
- *PTFE encapsulated silicone* (TES) gaskets - maximum operating temperature **225°F (107°C)**
- maximum operating temperatures for specific chemicals may be lower, contact Dixon® for specific recommendations




Size	<i>PTFE (FEP) encapsulated silicone</i>		<i>PTFE (FEP) encapsulated FKM</i>	
	Part #	Price/E	Part #	Price/E
¾"	75-G-TES	\$33.00	75-G-TEV	\$50.00
1"	100-G-TES	33.00	100-G-TEV	49.60
1¼"	125-G-TES	37.75	125-G-TEV	55.00
1½"	150-G-TES	38.30	150-G-TEV	59.00
2"	200-G-TES	40.00	200-G-TEV	60.60
2½"	250-G-TES	48.20	250-G-TEV	79.60
3"	300-G-TES	55.00	300-G-TEV	83.50
4"	400-G-TES	74.00	400-G-TEV	121.00

Cam & Groove Accordion Gaskets

Features:

- *PTFE* accordion gaskets (TFACC) are recommended for use with viscous (thick) fluids only
- maximum operating temperatures for specific chemicals may be lower, contact Dixon® for specific recommendations



Size	<i>PTFE (TFE)</i>	
	Part #	Price/E
¾"	75GTFACC	\$14.80
1"	100GTFACC	16.00
1¼"	125GTFACC	20.90
1½"	150GTFACC	19.00
2"	200GTFACC	22.00
3"	300GTFACC	48.00

The torque (force) required to close the handles on a pair of cam & groove fittings will vary according to the gasket chosen. Due to the nature of the PTFE material, the various PTFE gasket designs will require the most torque, increasing as you go from envelope to encapsulated, and finally, accordion.