## **Railroad Tank Car Connections**

### Features:

all swivel nuts have standard 5" Railroad Tank Car thread supplied with a Buna-N gasket in the threaded end, other gaskets available on page 69 also available in other materials and in 2" and 2½" sizes, consult Dixon™ for pricing and availability

# Style A





Stainless steel railroad tank car connections are not compatible with aluminum and brass.


					BIEW	
Male	Swivel	Elbow	316 Stainless Steel		Aluminum	
Adapter	Nut	LIDOW	Part #	Price/E	Part #	Price/E
3"	5"	120°	RTCA30	\$815.00		
4"	5"	110°	RTCA401	1027.95	ATCA40	\$712.15

<sup>&</sup>lt;sup>1</sup> parts are produced as a welded fabrication

# Style F

### Features:

- 4" TTMA flange can be bolted to sight glass; API adapter or other dry disconnect
- supplied with PTFE Buna-N envelope gasket



ATCF40

# Style GF

### Feature:

• 4" TTMA flange can be bolted to sight glass; API adapter or other dry disconnect

	TTMA	Boss-lock	Aluminum			
	Flange	Coupler	Part #	Elbow	Description	Price/E
	<b>4</b> "	4"	ATCGF40	110°	railroad tank car connections	\$530.25
NE	4"	4"	ATCGF40-90	90°	railroad tank car connections	590.85



## **Cam and Groove Screen**

Style S

## Feature:

stainless steel screen encapsulated in a buna gasket

0:	Hole Size	316L Stainless Steel		
Size		Part #	Price/E	
4"	1"	400-G-BUSS	\$150.00	



### Feature:

• 110° elbow

01 1 0:	Swivel Nut	Aluminum <sub>.</sub>		
Shank Size		Part #	Price/E	
4"	5"	ATCS40	\$334.50	

<sup>&</sup>lt;sup>1</sup> part is produced as a welded fabrication