

Double Clapper Siamese Connections

**Features:**

- double drop clapper with (2) pin lug swivel inlets provides required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply (250 GPM minimum per inlet)
- exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes
- maximum operating pressure: **175 PSI** at 70°F (21°C)
- finish: -P polished or -C polished chrome plated
- U/L listed and FM approved


back outlet

Outlet Female NPT	(2) Inlets Female	Branding	Cast Brass Part #	Price
4"	2½" NST(NH)	AutoSprinkler	DCS4025F	\$855.70
		AutoSprinkler	DCS4025F-P	969.70
		AutoSprinkler	DCS4025F-C	1036.40
		StandPipe	DCS4025F-SP	855.70
		No Branding	DCS4025F-NB	855.70
4"	3" NST(NH)	AutoSprinkler	DCS4030F	878.80
	3" NST(NH)	AutoSprinkler	DCS4030NYFD	878.80
6"	2½" NYFD	AutoSprinkler	DCS6025F	1018.50
	2½" NST(NH)	StandPipe	DCS6025F-SP	1018.50



Dimensions

Size	A	B
4" x 2½" x 2½"	9⅝"	12¼"
6" x 2½" x 2½"	10¼"	11¾"
4" x 3" x 3"	10"	12½"
6" x 3" x 3"	10⅜"	12½"



bottom outlet


Outlet Female NPT	(2) Inlets Female	Branding	Cast Brass Part #	Price
4"	2½" NST(NH)	AutoSprinkler	90DCS4025F	\$847.10
		AutoSprinkler	90DCS4025F-P	968.35
		AutoSprinkler	90DCS4025F-C	998.65
		StandPipe	90DCS4025F-SP	847.10
		No Branding	90DCS4025F-NB	847.10
4"	3" NST(NH)	AutoSprinkler	90DCS4030F	940.00
	3" NYFD	AutoSprinkler	90DCS4030NYFD	940.00
		StandPipe	90DCS4030NYFDSP	940.00
6"	2½" NST(NH)	AutoSprinkler	90DCS6025F	892.20
		StandPipe	90DCS6025F-SP	892.20
	3" NYFD	AutoSprinkler	90DCS6030NYFD	2072.35



P

Dimensions

Size	A	B	C
4" x 2½" x 2½"	11¾"	9⅝"	7¼"
6" x 2½" x 2½"	11¾"	10¾"	7¼"
4" x 3" x 3"	12½"	10⅞"	7½"
6" x 3" x 3"	12¼"	10⅞"	7¼"



- special threads, branding and finishes are available, consult Dixon™ for information
- replacement swivels can be ordered on page 581