FIoMAX Diesel Fueling System Diesel Fuel Gravity Fill Receivers

GFR-0 D



used with the FN600 or FN600BL to convert to gravity fueling

Size	Description	Anodized Aluminum	
Size	Description	Part #	Price/E
13⁄8"	straight	GFR-0	\$440.75
13⁄8"	45°	GFR-45	466.95
13⁄8"	90°	GFR-90	466.95
1"	straight	GFR1-0	466.95
1"	45°	GFR1-45	488.75
1"	90°	GFR1-90	488.75

FIOMAX Fuel Vents



Features:

Feature:

- 2" male NPT
- billet cap provides superior impact resistance
- easily serviced all metal construction
- rigid ball cage for positive seal
- available with: threaded outlet, half coupling and anti-vandalism mounting

Description	Part #	Price/E
vent with 5" tube	VT	\$405.85
vent with 7" tube	VT7	418.95
vent with 9" tube	VT9	432.00
vent with 5" tube and threaded outlet	VTT	453.85

High Flow FloMAX Fuel Vents

Feature:

Features:

7" tubes are available, contact Dixon[™] for more information

Description	Part #	Price/E
high flow fuel vent with 5" tube	VTX	\$754.95
high flow fuel vent with 9" tube	VTX-9	789.85



double

Diesel Fuel Swivels

- stainless steel male threaded base and ball bearings
- hard black anodized female threaded nut
- fluorosilicone sealing O-rings

Thread Size	Description	Part #	Price/E
1 ¹ / ₂ " male NPT x 1 ¹ / ₂ " female NPT	standard	FNS	\$314.20
2" male NPT x 11/2" female NPT	standard	FNS2	327.30
1 ¹ / ₂ " female NPT x 1 ¹ / ₂ " female NPT	double	FNSID	353.50
1½" male NPS x 1½" female NPT	standard	FN600S ¹	314.20

¹ used with FN600 or FN600BL

FIOMAX Service Box



Features:

- Designed to enclose receivers for diesel fuel, hydraulic oil, transmission fluid and coolant reducing contamination and weather related problems.
- normally installed on heavy duty earth mover equipment and drill rigs
- 12 gauge steel construction with heavy duty hinges •
- painted white Imron® Primer

	Part #	Price/E
ratoly	FSB	\$1669.85