

Surelock™ Quick Acting Couplings

Applications:

- multi-purpose coupling for water and air, commonly used in construction and mining; excels in services where ease, economy, safety and speed are paramount

Features:

- pressure activated gasket allows for easy coupling (less than 15 lbs. of force is required to connect the coupling gaskets seal upon introduction of line pressure)
- working pressure: **200 PSI** at ambient temperature (70°F)
- body: SG iron AS1831 400-250-12
- bellow seal: natural rubber (patent pending), other seal material available upon request
- safety pin is supplied with each coupling and is required as a safety precaution



Hose Ends




Head	Size	Part #	Price/E	Pkg Qty
small	3/8"	SL038H	\$10.40	50
	1/2"	SL050H	12.25	50
	3/4"	SL075H	12.40	50
	1"	SL100H	14.50	50
medium	1 1/2"	SL150H	40.50	15
	2"	SL200H	48.50	10

Male NPT Ends



Head	Size	Part #	Price/E	Pkg Qty
small	3/8"	SL038M	\$14.40	50
	1/2"	SL050M	14.20	50
	3/4"	SL075M	13.60	50
	1"	SL100M	13.90	50
medium	1 1/2"	SL150M	40.00	15
	2"	SL200M	42.00	15

Female NPT Ends



Head	Size	Part #	Price/E	Pkg Qty
small	3/8"	SL038F	\$14.20	50
	1/2"	SL050F	14.90	50
	3/4"	SL075F	12.80	50
	1"	SL100F	14.20	50
medium	1 1/2"	SL150F	37.50	15
	2"	SL200F	38.25	15

Surelock™ Quick Acting Couplings with Ferrules

Features:

- design provides quick, easy and effective coupling of air hose
- interlocking ferrule can be crimped or swaged to achieve maximum coupling sealing and retention with a low profile streamline appearance, see page 858 for crimp recommendations
- Dixon™ recommends that all hose assemblies be tested in accordance with ARPM testing procedures.
- working pressure: **200 PSI** at ambient temperature (70°F)
- for air and water service only



Head	Size	Hose OD		Part #	Price/E
		From:	To:		
small	1/2"	1/2"	1-2/64"	SL050CR	\$16.40
	3/4"	3/4"	1-22/64"	SL075CR	17.90
	1"	1"	1-46/64"	SL100CR	18.50