

## Pressure Spray Guns


**Features:**

- 3/8" female inlet
- 1/4" female outlet
- temperatures to **300°F**
- anti-fatigue pressure compensating design
- W = weeping, for the car wash industry, allows a small stream of water / leak

Part #	Maximum PSI	GPM	Price/E
<b>HPSG</b>	<b>5075</b>	12.0	<b>\$81.40</b>
<b>HPSGW</b>	<b>5000</b>	10.6	<b>94.05</b>

H


**Features:**

- 3/8" female inlet
- 1/4" female outlet
- **8 GPM**
- working pressure: **3700 PSI**
- maximum temperature to **320°F**

Part #	Price/E
<b>HPSGC</b>	<b>\$62.80</b>


**Features:**

- 3/8" female inlet
- 1/4" female outlet
- **8 GPM**
- working pressure: **5000 PSI**
- maximum temperature: **300°F**
- heavy duty anti-fatigue design
- stainless inner tube
- Zytel® housing

Part #	Price/E
<b>HPSGHD</b>	<b>\$103.75</b>


**Features:**

- 3/8" female inlet
- 22 mm x 14 mm female outlet
- **8 GPM**
- working pressure: **3700 PSI**
- maximum temperature: **140°F**
- extension length: 19"

Part #	Price/E
<b>AL9</b>	<b>\$73.00</b>


**Features:**

- gun: 22 mm male inlet ,22 mm x 14 mm female outlet end, working pressure **2500 PSI**
- lance: 18" with vari-spray nozzle 1.25 mm with 22 mm male inlet
- hose: 25', 1/4" ID with 22 mm x 14 mm female ends
- nozzle: 4.0 variable nozzle 0° to 80°

Part #	Price/E
<b>BIT-KIT</b>	<b>\$188.00</b>