


## Air King™ with Ferrules

### Features:

- working pressure: **150 PSI** at ambient temperature (70°F)
- design provides quick, easy and effective coupling of air hose
- interlocking ferrule can be crimped or swaged to achieve maximum coupling sealing and retention with a low profile streamline appearance, for crimp or swage diameter recommendations see page 856
- for air and water service only 

Style	Hose OD		Iron		316 Stainless Steel	
	From	To	Part #	Price/E	Part #	Price/E
1/2"	5/4"	1-2/64"	<b>AM1WF</b>	<b>\$15.00</b>	---	---
3/4"	1-4/64"	1-22/64"	<b>AM6WF</b>	<b>12.45</b>	<b>RAM6WF</b>	<b>\$64.00</b>
1"	1-18/64"	1-34/64"	<b>AM11WF-1</b>	<b>22.00</b>	---	---
1"	1-30/64"	1-46/64"	<b>AM11WF</b>	<b>16.90</b>	---	---



F

## Air King™ with Gauge Port

### Features:


- drilled with 1/4" NPT port for mounting a gauge
- gauge sold separately

Size	Iron		316 Stainless Steel	
	Part #	Price/E	Part #	Price/E
3/4"	<b>AM7T</b>	<b>\$24.30</b>	<b>RAM7T</b>	<b>\$76.00</b>



## Air King™ Universal Swivels

### Features:

- working pressure: **150 PSI** at ambient temperature (70°F)
- interchanges with other Air King™ fittings
- includes a heavy-duty, free-turning joint that swivels under pressure to prevent hose kinking
- for air and water service only 



hose end



male NPT



female NPT

Style	Iron		Iron		Iron	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
1/2"	---	---	<b>AM2SWIV</b>	<b>\$63.75</b>	---	---
3/4"	<b>AM6SWIV</b>	<b>\$74.50</b>	<b>AM7SWIV</b>	<b>63.25</b>	<b>AM8SWIV</b>	<b>\$66.60</b>



Air King™ is for air and water service only *Warning: Never use any Air King™ coupling for steam service! None of Dixon™'s catalog information is to be interpreted to mean that this type of coupling is suitable for use on steam hose.*

## Compressor Y

### Feature:

- converts a single supply source to a dual outlet

Female NPT Inlet (1)	Male NPT Outlets (2)	Iron	
		Part #	Price/E
1"	3/4"	<b>Y10075</b>	<b>\$59.75</b>

