



Brass Electrical Fire All-Fog Nozzles



Features:

- maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)
- delivers 30° - 60° - 90° fog pattern - shutoff to 30° fog, adjustable to 90° fog
- U/L listed and Factory Mutual approved for class C fires
- supplied with bumper
- Use of this nozzle is not likely to prove hazardous when nozzle is held in excess of 10 feet from electrical apparatus and circuits not involving more than 250,000 volts. 

Size	Thread	90° Spray GPM @ 100 PSI	Brass Part #	Price/E
1½"	NST (NH)	90	BFNE150NST	\$234.30
1½"	NPSH	90	BFNE150	234.30

Ball Shutoffs

Features:

- full time swivel base ensures the durable rubber-like handle can be positioned for easy operation
- maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)



Thread	Length	Waterway	Cast Brass Part #	Price/E
1½" NST (NH)	4¾"	1-3/8"	BSO150NST	\$1363.75
1½" NPSH	4¾"	1-3/8"	BSO150S	1363.75

Replacement Part

Description	Composite Part #	Price/E
replacement handle	BSO150-H	\$81.95

Nozzle Tips

Features:

- straight stream only
- maximum operating pressure: **100 PSI** (water only) at 70°F (21°C)
- 74 GPM @ 100 PSI



Thread	Length	Orifice	Satin Brass Part #	Price/E
1" NST (NH)	4-3/4"	1/2"	BNT100F	\$154.15
1" NPSH	4-3/4"	1/2"	BNT100S	154.15
1½" NST (NH)	4-3/8"	1/2"	BNT150F	181.15
1½" NPSH	4-3/8"	1/2"	BNT150S	222.25

P