


Clamps

Dairy Clamps - 13WGC




Tube OD	Service Pressure Rating @ 70°F ¹	Dimension A	304 Stainless Steel	
			Part #	Price/E
1" - 1½"	80	2.080"	13WGC100-150	\$12.80
2"	80	2.610"	13WGC200	13.40
2½"	60	3.140"	13WGC250	16.45
3"	40	3.670"	13WGC300	17.70
4"	40	4.780"	13WGC400	21.00

¹ finger tight

Accessories

Spring Loaded Nut - 13SLN



Features:

- Beneficial for lines using PTFE gaskets that are subject to large temperature swings, as the PTFE is compressed through the cycling of the lines, the spring load will help keep the connection from leaking.
- If the lines suffer from vibration and bolted clamps are not an option, refitting single pin clamps with this nut will keep the connections from leaking for a longer time than with standard wing nuts.
- Spring loaded nuts can add a level of insurance to shipments, of transported material in tanks via truck, where vibrations can loosen the standard single pin clamps.
- can be used on all wing nut style clamps
- torque to 50 in. lb.

Thread	Dimension A	Dimension B	304 Stainless Steel	
			Part #	Price/E
5/16 - 18	1.73"	.875"	13SLN	\$92.25

N

Nuts and Bolts



Description	Part #	Price/E
cross hole wing nut 5/16"-18	13WNX	\$11.70
mini cross hole wing nut 5/16"-18, for ½" - ¾" clamps	13WNXM	11.70
serrated wing nut 5/16"-18	13WNS	11.70
hex wing nut 5/16"-18	13WNH	7.80
bronze hex nut ⅝"-16, for bolted clamps	13BN	2.95
bolt 3/8"-16 x 2¼", for 1½" bolted clamps	13CB-2.25	9.50
bolt 3/8"-16 x 2¾", for 2" and 2½" bolted clamps	13CB-2.75	9.50
bolt 3/8"-16 x 3¼", for 3" - 12" bolted clamps	13CB-3.25	9.50
rivet pin, for ½" - 5" single pin clamps 5/16" x 1"	13RP	4.45
rivet pin, for 6" and 8" single pin clamps 5/16" x 1⅝"	13RP6	5.50
5/16"-18 x 2" threaded eye bolt, for ½" - 5" clamps	13IB	3.65
5/16"-18 x 2½" threaded eye bolt, for 6" - 12" clamps	13IB6	3.65
brass ⅝"-16 nuts, for 10" and 12" bolted clamps	13BNH	4.35
stainless steel hex nut, for bolted clamps	13SN	3.75
⅜" lockwasher 304 stainless steel, for bolted clamps	13LW	1.90