

## Legris In-Line Check Valves

### Features:

- allows air to pass in one direction while blocking flow in the other direction, a pressure of more than 7 PSI will overcome the spring pressure and allow flow
- arrow indicates free flow direction
- maximum operating pressure: **145 PSI** at ambient temperature (70°F)

Tube OD	Part #	Price/E	Pkg Qty
5/32"	<b>79960400</b>	<b>\$28.35</b>	10
6mm	<b>79960600</b>	<b>30.35</b>	10
1/4"	<b>79965600</b>	<b>31.55</b>	10
5/16"	<b>79960800</b>	<b>36.30</b>	10



F

## Legris In-Line Check Valves

### Application:

- compact and lightweight design makes these meter out check valves suitable as a safety item in compressed air circuits

### Features:

- allows air to pass in one direction while blocking flow in the other direction
- arrow on body of the fitting indicates direction of flow, a pressure of more than 7 PSI will overcome spring pressure keeping the valve closed, thus allowing the passage of air
- pressure range: **15 PSI** to **145 PSI** at ambient temperature (70°F)
- body: nylon with nickel plated brass base
- pre-applied thread sealant on tapered threads

Tube OD	NPT Size	Part #	Price/E
5/32"	10-32 <sup>1</sup>	<b>79940420</b>	<b>\$32.60</b>
5/32"	1/8"	<b>79950411</b>	<b>27.75</b>
1/4"	1/8"	<b>79955611</b>	<b>31.05</b>
1/4"	1/4"	<b>79955614</b>	<b>31.55</b>
3/8"	1/4"	<b>79956014</b>	<b>38.75</b>
3/8"	3/8"	<b>79956018</b>	<b>43.85</b>



<sup>1</sup> UNF - Straight thread, supplied with gasket

## Stainless Steel Legris Uni-Directional Check Valves

### Features:

- blocks the fluid passage when the pressure differential is lower than 3.6 PSI
- pressure range: **7 PSI** to **580 PSI**
- temperature range: **-4°F** to **356°F**
- body: 316L stainless steel
- shut-off valve: 316L stainless steel
- return spring: 302 stainless steel
- seals: FKM

NPT Thread	Part #	Price/E
1/8"	<b>48951111</b>	<b>\$178.25</b>
1/4"	<b>48951414</b>	<b>178.25</b>
3/8"	<b>48951818</b>	<b>216.25</b>
1/2"	<b>48952222</b>	<b>214.95</b>

