

Dixon™ Type C Couplers

female coupler x hose shank

C

Features:

- Finger rings are not supplied on ½" - 1" Dixon™ couplings.
- ½" Dixon coupler has only one cam arm.
- Couplers are supplied standard with a Buna-N gasket. Other gasket types are available on pages 78-79.



356T6 aluminum



aluminum hard coat



brass

Size	356T6 Aluminum		Aluminum Hard Coat		Brass	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
½"	50-C-AL	\$21.50	---	---	50-C-BR	\$46.40
¾"	75-C-AL	24.70	---	---	75-C-BR	50.95
1"	100-C-AL	27.30	---	---	100-C-BR	62.05
1¼"	125-C-AL	57.00	---	---	125-C-BR	88.00
1½"	150-C-AL	34.75	150-C-ALH	\$46.00	150-C-BR	83.60
2"	200-C-AL	37.95	200-C-ALH	57.30	200-C-BR	105.90
2½"	250-C-AL	69.65	---	---	250-C-BR	136.00
3"	300-C-AL	60.00	300-C-ALH	87.95	300-C-BR	189.00
4"	400-C-AL	81.60	400-C-ALH	111.40	400-C-BR	238.00
5"	500-C-AL	123.85	---	---	---	---
6"	600-C-AL	195.95	600-C-ALH	251.00	600-C-BR	814.90
8"	800-C-AL ¹	757.00	---	---	---	---



¹ Dixon™ and Boss-Lock™ cam and groove couplings *do not interchange in the ½" and 8" sizes*. The 8" Dixon™ design has 4 cam arms, Boss-Lock™ design has 2 cam arms.



unplated malleable iron



316 stainless

Size	Unplated Malleable Iron		316 Stainless Steel	
	Part #	Price/E	Part #	Price/E
½"	---	---	50-C-SS	\$57.60
¾"	---	---	75-C-SS	69.10
1"	---	---	100-C-SS	79.30
1¼"	---	---	125-C-SS	138.40
1½"	150-C-MI	\$51.55	150-C-SS	96.60
2"	200-C-MI	54.00	200-C-SS	114.25
2½"	---	---	250-C-SS	292.50
3"	300-C-MI ^{1, 2}	87.00	300-C-SS	198.70
4"	400-C-MI ^{1, 2}	112.20	400-C-SS	336.00
5"	---	---	500-C-SS	474.00
6"	600-C-MI ^{1, 2}	210.00	600-C-SS	548.00

¹ Suitable for use with King Crimp™ sleeves and ferrules, see pages 14-17.

² ductile iron