

Caps and Plugs

Polycarbonate Breakable Cap

Application:

- prevents entry of foreign material and protects female threads on pin lug fire department inlet connections

Feature:

- used on pin lug females




Size	Polycarbonate Part #	Price/E
2½"	PBC250	\$8.00

Aluminum Breakable Cap

Features:

- for use on fire department inlet connections
- prevents entry of foreign matter and protects female threads
- breakable ears feature permits fast hose connection
- two eyebolts with nuts for attachment to female pin lug swivel
- painted red finish



Size	Aluminum Part #	Price/E
2½"	ABC250	\$10.90

FDC Plug

Features:

- fits standard 2½" NST female swivel
- withstands wide range of temperatures from **-4°F to 200°F (-20°C to 93°C)**
- 1½" pentagonal nut with weep hole to allow for drainage
- removed from FDC with adjustable hydrant wrench



NST (NH) Thread	Polycarbonate Part #	Price/E
2½"	PP250F	\$12.00

Adjust-A-Plug

Features:

- molded red polycarbonate protective plug for swivel connections up to 2½"
- two adjustable metal plates installed in the back of the plug can be mated with your local thread
- plug can be easily removed with a fire department spanner wrench



front



back

Polycarbonate Part #	Price/E
PAP250	\$8.00