

Dixon™ Cam and Groove with Notched NOS Shank

Features:

- system allows you to better manage your inventories, you can stock one stem and two ferrules, and cover the same hose range with less inventory, *you must purchase a fitting and the matching ferrule to create an assembly*
- for hose outside diameters of 2-4/64" and below, *the couplings are crimp only*
- for hose outside diameters of 2-5/64" and above, the couplings can be crimped or swaged
- for use with notched ferrules at bottom of the page
- see pages 289 and 439 for male NPT notched NOS fittings



Only use the NOS shank with the NOS ferrules.


Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturer's stems or ferrules with Dixon™ products.

Couplers

Dixon™ type C with NOS shank


316 Stainless Steel		
Size	Part #	Price/E
1½"	150CNOSSS ¹	\$82.40
2"	200CNOSSS	85.10
3"	300CNOSSS	168.90

¹ part will be discontinued as stock is depleted



crimped assembly

Contact Dixon™ for swage and crimp recommendations.



swaged assembly



female coupler x
notched NOS hose shank

Adapters

type E with NOS shank

316 Stainless Steel		
Size	Part #	Price/E
1½"	150ENOSSS ¹	\$38.00
2"	200ENOSSS	50.60
3"	300ENOSSS	103.55

¹ part will be discontinued as stock is depleted



swaged assembly

Contact Dixon™ for swage and crimp recommendations.



crimped assembly



male adapter x
notched NOS hose shank

Notched NOS Ferrules

Size	Hose OD		304 Stainless Steel	
	from	to	Part #	Price/E
1½"	1-60/64"	2-12/64"	<i>GAS2334NOS</i>	\$32.30
1½"	2-4/64"	2-22/64"	<i>GAS2370NOS</i>	34.50
2"	2-30/64"	2-44/64"	<i>GAS2709NOS</i>	31.50
2"	2-42/64"	2-54/64"	<i>GAS2885NOS</i>	64.40
3"	3-30/64"	3-46/64"	<i>GAS3760NOS</i>	46.35
3"	3-47/64"	3-54/64"	<i>GAS3885NOS</i>	63.00

