

Notched Cam and Groove

Features:

- coupling can be removed from a damaged hose by cutting away the ferrule, without necessarily damaging the fitting, *after inspection of the fitting to determine its suitability for reuse*, it can be reinstalled into another hose by using a *new ferrule*
- system allows you to better manage your inventories, you can stock one coupling and two ferrules, and cover the same hose range with less inventory, *you must purchase a fitting and the matching ferrule to create an assembly*
- for use with notched ferrules on previous page



Dixon™ stems and ferrules are specifically designed to be used together as a coupling system. Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturer's stems or ferrules with Dixon™ products.

Couplers

EZ Boss-Lock™ type C with notched shank



female coupler x notched hose shank


| Size | 316 Stainless Steel | |
|------|---------------------|-----------------|
| | Part # | Price/E |
| 1½" | RC150EZNO | \$113.75 |
| 2" | RC200EZNO | 121.30 |
| 3" | RC300EZNO | 208.20 |
| 4" | RC400EZNO | 310.85 |

Boss-Lock™ type C with notched shank




female coupler x notched hose shank

| Size | 316 Stainless Steel | |
|------|---------------------|-----------------|
| | Part # | Price/E |
| 1½" | RC150BLNO | \$122.75 |
| 2" | RC200BLNO | 116.80 |
| 3" | RC300BLNO | 199.40 |
| 4" | RC400BLNO | 297.00 |



crimped assembly

Contact Dixon™ for swage and crimp recommendations.



swaged assembly

Adapters

Boss-Lock™ type E with notched shank



male adapter x notched hose shank

| Size | 316 Stainless Steel | |
|------|---------------------|----------------|
| | Part # | Price/E |
| 1½" | RE150NO | \$61.00 |
| 2" | RE200NO | 65.30 |
| 3" | RE300NO | 126.00 |
| 4" | RE400NO | 246.90 |



swaged assembly

Contact Dixon™ for swage and crimp recommendations.



crimped assembly