

Synthetic Single Jacket Mill Hose

Application:

- Used in open end water discharge applications only. Not intended for fire fighting service.



Features:

- outer construction: single jacket, all polyester
- tube construction: black, PVC rubber
- rated pressure: **250 PSI** at ambient temperature (70°F)
- working pressure: **112 PSI** at ambient temperature (70°F)
- Consult Dixon™ for pricing and availability on 75' lengths and other threads and configurations.

Coupled with NPSH female and male expansion ring couplings



Size	Length	Part #	Price
1½"	50'	M15-50RAS	\$204.50
1½"	100'	M15100RAS	284.40
2"	50'	M20-50RAS	284.40
2"	100'	M20100RAS	383.30
2½"	50'	M25-50RAS	315.30
2½"	100'	M25100RAS	474.50

Coupled with NST female and male expansion ring couplings



Size	Length	Part #	Price
1½"	50'	M15-50RAF	\$194.75
1½"	100'	M15100RAF	284.40
2½"	25'	M25-25RAF	225.25
2½"	50'	M25-50RAF	315.30
2½"	100'	M25100RAF	474.50

Coupled with MNPT x MNPT male expansion ring couplings



Size	Length	Part #	Price
1½"	50'	M15-50RAT	\$234.40
1½"	100'	M15100RAT	329.90
2"	50'	M20-50RAT	284.40
2"	100'	M20100RAT	393.80

- 75' lengths and other threads and configurations are available, contact Dixon™