

300# Single Jacket All Polyester Fire Hose

Features:

- outer construction: single jacket, all polyester
- tube construction: EPDM rubber lining
- proof pressure: **300 PSI**
- service test pressure: **150 PSI** at ambient temperature (70°F)
- working pressure: **135 PSI** at ambient temperature (70°F)
- 25' and 75' lengths, U/L labeled hoses and other threads and configurations are available, contact Dixon™



Uncoupled

Size	Bowl	Length	Part #	Price/E
1½"	1-3/4"	50'	A315-50UC	\$174.80
1½"	1-3/4"	100'	A315-100UC	349.60
2"	2-1/4"	50'	A320-50UC	296.80
2"	2-1/4"	100'	A320-100UC	593.55
2½"	2-13/16"	50'	A325-50UC	369.85
2½"	2-13/16"	100'	A325-100UC	612.50
3"	3-3/8"	50'	A330-50UC	498.85
3"	3-3/8"	100'	A330-100UC	997.70

Coupled with female and male expansion ring couplings



Size	Length	Part #	Rocker Lug	Rocker Lug	Pin Lug	Rocker Lug
			Aluminum NST (NH) RAF	Brass NST (NH) RBF	Brass NST (NH) PBF	Aluminum NPSH RAS
1½"	50'	A315-50	\$266.25	\$336.80	\$321.25	\$279.10
1½"	100'	A315100	484.00	530.35	562.30	460.95
2"	50'	A320-50	---	---	---	566.60
2"	100'	A320100	---	---	---	901.70
2½"	50'	A325-50	430.10	664.55	742.70	430.10
2½"	100'	A325100	828.75	1001.30	1002.50	828.75
3"	50'	A330-50	---	---	---	841.95
3"	100'	A330100	---	---	---	1365.85

- other threads and configurations available, contact Dixon™