

## Marine Grade Worm Gear Clamps

### Features:

- three-piece construction
- clamp meets SAEJ1508 which supercedes Mil Spec WW-C-440B
- 316 marine grade SS: band, screw, housing
- screw design: 5/16" slotted hex head
- suggested installation torque 30-42 inch pounds, maximum recommended torque 60 in. lbs.
- **all clamps sold 10 per box**



- Torque ratings correspond to the torque rating of the screw of the clamp and *are not an indication of the working pressure of any hose assembly installed with this clamp.*

| Band Width | Hose OD  |         | 316 Stainless Steel Part # | Price/Each    |
|------------|----------|---------|----------------------------|---------------|
|            | from     | to      |                            |               |
| 1/2"       | 3/8"     | 7/8"    | <b>MGC6</b>                | <b>\$2.95</b> |
|            | 7/16"    | 1"      | <b>MGC8</b>                | <b>2.95</b>   |
|            | 9/16"    | 1-1/16" | <b>MGC10</b>               | <b>2.95</b>   |
|            | 9/16"    | 1-5/16" | <b>MGC12</b>               | <b>3.05</b>   |
|            | 11/16"   | 1-1/2"  | <b>MGC16</b>               | <b>3.05</b>   |
|            | 3/4"     | 1-3/4"  | <b>MGC20</b>               | <b>3.05</b>   |
|            | 1-1/16"  | 2"      | <b>MGC24</b>               | <b>3.05</b>   |
|            | 1-5/16"  | 2-1/4"  | <b>MGC28</b>               | <b>3.10</b>   |
|            | 1-9/16"  | 2-1/2"  | <b>MGC32</b>               | <b>3.10</b>   |
|            | 1-13/16" | 2-3/4"  | <b>MGC36</b>               | <b>3.20</b>   |
|            | 2-11/16" | 3"      | <b>MGC40</b>               | <b>3.40</b>   |
|            | 2-5/16"  | 3-1/4"  | <b>MGC44</b>               | <b>3.95</b>   |
|            | 2-9/16"  | 3-1/2"  | <b>MGC48</b>               | <b>3.95</b>   |
|            | 2-13/16" | 3-3/4"  | <b>MGC52</b>               | <b>4.20</b>   |
|            | 3-1/16"  | 4"      | <b>MGC56</b>               | <b>4.20</b>   |
|            | 2-1/2"   | 4-1/2"  | <b>MGC64</b>               | <b>4.65</b>   |
|            | 3-1/16"  | 5"      | <b>MGC72</b>               | <b>4.80</b>   |
|            | 3-1/2"   | 5-1/2"  | <b>MGC80</b>               | <b>5.30</b>   |
|            | 4-3/32"  | 6"      | <b>MGC88</b>               | <b>5.45</b>   |
|            | 4-1/2"   | 6-1/2"  | <b>MGC96</b>               | <b>5.65</b>   |
|            | 5"       | 7"      | <b>MGC104</b>              | <b>5.70</b>   |



K

## Aero-Seal® Clamps

### Features:

- four-piece construction
- band slots designed for strength and smooth action
- saddle interlocks into embossed band to form a true concentric circle
- slotted hex head screw design
- heat treated screws have buttress thread type
- safety collar or thumb screw available on the style 200 series only
- suggested installation torque 30-42 inch pounds, maximum recommended torque 60 in. lbs.
- **all clamps sold 10 per box**



- Torque ratings correspond to the torque rating of the screw of the clamp and *are not an indication of the working pressure of any hose assembly installed with this clamp.*

#### Style 100:

- band and housing: 300 SS
- screw: plated carbon steel

#### Style 200:

- band and housing: 300 SS
- screw: 410 stainless steel

#### Style 300:

- band and housing: 302 SS
- screw: 305 stainless steel

| Band Width | Hose OD  |         | Style 100    |               | Style 200    |               | Style 300    |               | Pkg Qty |
|------------|----------|---------|--------------|---------------|--------------|---------------|--------------|---------------|---------|
|            | from     | to      | Part #       | Price/E       | Part #       | Price/E       | Part #       | Price/E       |         |
| 9/16"      | 7/16"    | 25/32"  | <b>10006</b> | <b>\$1.95</b> | <b>20006</b> | <b>\$2.40</b> | <b>30006</b> | <b>\$2.75</b> | 10      |
|            | 1/2"     | 29/32"  | <b>10008</b> | <b>1.95</b>   | <b>20008</b> | <b>2.40</b>   | <b>30008</b> | <b>2.75</b>   | 10      |
|            | 9/16"    | 1-1/16" | <b>10010</b> | <b>1.95</b>   | <b>20010</b> | <b>2.40</b>   | <b>30010</b> | <b>2.75</b>   | 10      |
|            | 11/16"   | 1-1/4"  | <b>10012</b> | <b>2.05</b>   | <b>20012</b> | <b>2.50</b>   | <b>30012</b> | <b>2.85</b>   | 10      |
|            | 13/16"   | 1-1/2"  | <b>10016</b> | <b>2.05</b>   | <b>20016</b> | <b>2.50</b>   | <b>30016</b> | <b>2.85</b>   | 10      |
|            | 13/16"   | 1-3/4"  | <b>10020</b> | <b>2.05</b>   | <b>20020</b> | <b>2.50</b>   | <b>30020</b> | <b>2.90</b>   | 10      |
|            | 1-1/16"  | 2"      | <b>10024</b> | <b>2.05</b>   | <b>20024</b> | <b>2.50</b>   | <b>30024</b> | <b>2.90</b>   | 10      |
|            | 1-5/16"  | 2-1/4"  | <b>10028</b> | <b>2.10</b>   | <b>20028</b> | <b>2.60</b>   | <b>30028</b> | <b>2.95</b>   | 10      |
|            | 1-9/16"  | 2-1/2"  | <b>10032</b> | <b>2.10</b>   | <b>20032</b> | <b>2.60</b>   | <b>30032</b> | <b>2.95</b>   | 10      |
|            | 1-13/16" | 2-3/4"  | <b>10036</b> | <b>2.15</b>   | <b>20036</b> | <b>2.65</b>   | <b>30036</b> | <b>3.00</b>   | 10      |
|            | 1-1/16"  | 3"      | <b>10040</b> | <b>2.65</b>   | <b>20040</b> | <b>3.25</b>   | <b>30040</b> | <b>3.70</b>   | 10      |
|            | 2-5/16"  | 3-1/4"  | <b>10044</b> | <b>2.85</b>   | <b>20044</b> | <b>3.55</b>   | <b>30044</b> | <b>4.00</b>   | 10      |
|            | 2-9/16"  | 3-1/2"  | <b>10048</b> | <b>2.85</b>   | <b>20048</b> | <b>3.55</b>   | <b>30048</b> | <b>4.00</b>   | 10      |
|            | 2-13/16" | 3-3/4"  | <b>10052</b> | <b>3.05</b>   | <b>20052</b> | <b>3.80</b>   | <b>30052</b> | <b>4.25</b>   | 10      |
|            | 3-1/16"  | 4"      | <b>10056</b> | <b>3.05</b>   | <b>20056</b> | <b>3.80</b>   | <b>30056</b> | <b>4.25</b>   | 10      |
|            | 3-5/16"  | 4-1/4"  | <b>10060</b> | <b>3.30</b>   | <b>20060</b> | <b>4.10</b>   | <b>30060</b> | <b>4.60</b>   | 10      |



style 300