

Single Hydrant Gate Valves with Hand Wheel

**Application:**

- used to throttle the flow from a fire hydrant preventing damage to the hydrant

Features:

- O-ring seal
- U/L listed
- for use on standpipes and fire pumps where U/L listing is required
- maximum operating pressure: **175 PSI** (water only) at 70°F (21°C)
- other configurations are available, contact Dixon™ for additional information

Inlet Female	Outlet Male	Cast Red Brass Part #	Price
2½" NST (NH)	2½" NST (NH)	UHGV250F	\$450.00
2½" NST (NH)	2½" NST (NH)	UHGV250F-D	\$595.70

Replacement Part

Description	Part #	Price
handwheel	UHGV250-W	\$23.00



Single Hydrant Gate Valves with Speed Handle

Application:

- used to throttle the flow from a fire hydrant preventing damage to the hydrant

Features:

- pin lug swivel, non-rising stem, aluminum speed handle
- rubber seal
- for use on hydrants, standpipes, and fire pumps
- maximum operating pressure: **175 PSI** (water only) at 70°F (21°C)
- other configurations are available, contact Dixon™ for additional information

Inlet Female	Outlet Male	Cast Brass Part #	Price
2½" NST (NH)	2½" NST (NH)	HGV250F	\$318.00
2½" NST (NH)	2½" NST (NH)	HGV250F-D	\$499.00
2½" NST (NH)	2½" NPSH	HGV250	\$318.00

Replacement Part

Description	Aluminum Part #	Price
speed handle	HGV250-H	\$18.00



P