

Reusable Fittings

Applications:



Reusable fittings are recommended for low pressure air hose applications. They offer a more durable hose connection and are easily repaired. Maximum working pressure: **250 PSI** at ambient temperature (70°F). *Caution: Check hose OD and ID accurately before ordering.*



reusable ferrules

Hose ID	Hose OD	Brass Part #	Price/E	303 Stainless Steel Part #	Price/E	Opt Qty ¹
1/4"	1/2"	1800408F	\$2.79	1800408FSS	\$35.20	100
1/4"	9/16"	1800409F	3.32	1800409FSS	34.37	50
1/4"	5/8"	1800410F	3.56	1800410FSS	34.55	50
5/16"	9/16"	1800509F	5.12	1800509FSS	35.62	100
5/16"	5/8"	1800510F	3.96	1800510FSS	35.46	50
5/16"	11/16"	1800511F	5.85	---	---	50
3/8"	5/8"	1800610F	3.73	1800610FSS	35.71	50
3/8"	11/16"	1800611F	4.40	1800611FSS	36.00	50
3/8"	3/4"	1800612F	3.91	1800612FSS	35.80	50
1/2"	7/8"	1800814F	8.42	1800814FSS	52.37	25
1/2"	15/16"	1800815F	9.63	1800815FSS	52.37	25
1/2"	1"	1800816F	10.89	---	---	20

¹ stainless steel parts are packaged to order



reusable male stems

Hose ID	Male NPTF Thread ¹	Brass Part #	Price/E	303 Stainless Steel Part #	Price/E	Opt Qty ²
1/4"	1/8"	1820402S	\$5.48	1820402SS	\$29.27	100
1/4"	1/4"	1820404S	3.51	1820404SS	34.12	100
1/4"	3/8"	1820406S	6.52	---	---	50
5/16"	1/4"	1820504S	4.15	1820504SS	32.10	50
5/16"	3/8"	1820506S	6.60	---	---	50
3/8"	1/4"	1820604S	3.63	1820604SS	35.70	100
3/8"	3/8"	1820606S	4.32	1820606SS	35.64	50
3/8"	1/2"	1820608S	8.14	---	---	25
1/2"	1/4"	1820804S	8.12	---	---	50
1/2"	3/8"	1820806S	7.95	1820806SS	42.55	50
1/2"	1/2"	1820808S	8.37	1820808SS	50.90	25

¹ stainless steel parts have NPT threads

² stainless steel parts are packaged to order