


The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number 566 - 563, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	565
Cone Part Number	566
Cup Part Number	563
Design Units	Imperial
Bearing Weight	1.900 Kg 4.20 lb
Cage Type	Stamped Steel

Dimensions

d - Bore	69.850 mm 2.7500 in
-----------------	------------------------

D - Cup Outer Diameter	127 mm 5 in
B - Cone Width	36.170 mm 1.4240 in
C - Cup Width	28.575 mm 1.1250 in
T - Bearing Width	36.513 mm 1.4375 in

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius¹	3.560 mm 0.14 in
r - Cup Backface "To Clear" Radius²	3.30 mm 0.130 in
da - Cone Frontface Backing Diameter	77.98 mm 3.74 in
db - Cone Backface Backing Diameter	85.09 mm 3.35 in
Da - Cup Frontface Backing Diameter	119.90 mm 4.75 in
Db - Cup Backface Backing Diameter	112.01 mm 4.41 in
Ab - Cage-Cone Frontface Clearance	2.8 mm 0.11 in
Aa - Cage-Cone Backface Clearance	2.5 mm 0.1 in
a - Effective Center Location³	-8.1 mm -0.32 in

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁴	50900 N 11400 lbf
---	----------------------

C1 - Dynamic Radial Rating (1 million revolutions)⁵	196000 N 44100 lbf
---	-----------------------

C0 - Static Radial Rating	262000 N 58900 lbf
----------------------------------	-----------------------

C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁶	31700 N 7130 lbf
---	---------------------

Factors

K - Factor⁷	1.61
-------------------------------	------

e - ISO Factor⁸	0.36
-----------------------------------	------

Y - ISO Factor⁹	1.65
-----------------------------------	------

G1 - Heat Generation Factor (Roller-Raceway)	101
---	-----

G2 - Heat Generation Factor (Rib-Roller End)	24
---	----

Cg - Geometry Factor	0.117
-----------------------------	-------

¹ These maximum fillet radii will be cleared by the bearing corners.

² These maximum fillet radii will be cleared by the bearing corners.

³ Negative value indicates effective center inside cone backface.

⁴ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.


⁵ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁶ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁷ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e 0.36
ISO Factor - Y 1.65
Bearing Weight 4.2 lb
Number of Rollers Per Row 20
Effective Center Location -0.32 inch



THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

566 - 563
TS BEARING ASSEMBLY

K Factor 1.61
Dynamic Radial Rating - C90 50900 lbf
Dynamic Thrust Rating - Ca90 31700 lbf
Static Radial Rating - C0 262000 lbf
Dynamic Radial Rating - C1 196000 lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY