


The Timken Company


4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number YCJT 1 3/8 SGT, Two-Bolt Flanged Units Setscrew Locking (Includes Industrial and Standard Series)



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#)

Specifications

Bore Size d	1 3/8 in 34.9 mm
Bearing Number	GY1106KRRB SGT
Dimension E	1.927 in 48.95 mm
Inside Ring Outside Diameter	1.843 in 46.8 mm
Series	Industrial
Weight	3.18 lb 1.44 Kg
Seal Type	Shroud Seal



Dimensions

Total Length H	155.6 mm 6.126 in
Total Height L	92.1 mm 3.626 in
Total Width A	1.252 in 31.8 mm
Bolt Hole Spacing J	130.2 mm 5.126 in
Bolt Hole Size N	13 mm 0.512 in
Flange Thickness A1	13.5 mm 0.531 in
Center of Bearing from Housing End A2	21.05 mm 0.829 in
Inside Ring Width B	45.2 mm 1.780 in
Center of Bearing from Bearing End S	21.05 mm 0.829 in

Basic Load Ratings

—

Static Load Rating	3400 lbf 15100 N
Dynamic Load Rating	6400 lbf 28500 N



Bearing Number	GY1106KRRB SGT			
Load Ratings - C _r	6400	lbf	28500	N
Load Ratings - C _{0r}	3400	lbf	15100	N
Weight		lb		kg
Bolt Size	M8x1.25			

TIMKEN

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

YCJT 1 3/8 SGT

Two-Bolt Flanged Units Setscrew Locking
(Includes Industrial and Standard Series)

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY