
The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number 3776 - 3720, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





Specifications | Dimensions | Abutment and Fillet Dimensions | Basic Load Ratings | Factors

Specifications

Series	3700
Cone Part Number	3776
Cup Part Number	3720
Design Units	Imperial
Bearing Weight	0.900 Kg 2.10 lb
Cage Type	Stamped Steel

Dimensions

d - Bore	44.983 mm 1.7710 in

D - Cup Outer Diameter	93.264 mm 3.6718 in
B - Cone Width	30.302 mm 1.1930 in
C - Cup Width	23.813 mm 0.9375 in
T - Bearing Width	30.163 mm 1.1875 in

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius[1]	3.560 mm 0.14 in
r - Cup Backface "To Clear" Radius[2]	3.30 mm 0.130 in
da - Cone Frontface Backing Diameter	53.09 mm 2.09 in
db - Cone Backface Backing Diameter	58.93 mm 2.32 in
Da - Cup Frontface Backing Diameter	87.90 mm 3.50 in
Db - Cup Backface Backing Diameter	82.04 mm 3.23 in
Ab - Cage-Cone Frontface Clearance	1.5 mm 0.06 in
Aa - Cage-Cone Backface Clearance	1.5 mm 0.06 in
a - Effective Center Location[3]	-8.1 mm -0.32 in


Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)[4]	31700 N 7120 lbf
C1 - Dynamic Radial Rating (1 million revolutions)[5]	122000 N 27500 lbf
C0 - Static Radial Rating	153000 N 34300 lbf
C_{a90} - Dynamic Thrust Rating (90 million revolutions)[6]	18300 N 4120 lbf

Factors

K - Factor[7]	1.73
e - ISO Factor[8]	0.34
Y - ISO Factor[9]	1.77
G1 - Heat Generation Factor (Roller-Raceway)	49.9
G2 - Heat Generation Factor (Rib-Roller End)	14.5
Cg - Geometry Factor	0.0903

[1] These maximum fillet radii will be cleared by the bearing corners.
[2] These maximum fillet radii will be cleared by the bearing corners.
[3] Negative value indicates effective center inside cone backface.
[4] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.
[5] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.
[6] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.
[7] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[8] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[9] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e	0.34	
ISO Factor - Y	1.77	
Bearing Weight	2.1	lb
Number of Rollers Per Row	18	
Effective Center Location	-0.32	inch

TIMKEN

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

3776 - 3720
TS BEARING ASSEMBLY

K Factor	1.73	
Dynamic Radial Rating - C90	31700	lbf
Dynamic Thrust Rating - Ca90	18300	lbf
Static Radial Rating - C0	153000	lbf
Dynamic Radial Rating - C1	122000	lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY