



The Timken Company


4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • Web site: www.timken.com

Part Number YTU SGT 1 11/16, Fafnir® Take-Up Units Setscrew Locking



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#)

Specifications

Shaft Size d	1 11/16 in 42.9 mm
Bearing Number	GY1111KRRB SGT
Dimension G	2.520 in 64 mm
Dimension P	2.098 in 53.3 mm
Dimension T	1.280 in 32.5 mm
Series	Industrial
Weight	6.95 lb 3.15 Kg
Seal Type	Shroud Seal
Housing Construction	Take-Up

Alternate Part Name

YTUSGT 1 11/16

Dimensions

Housing Width A 2.563 in
65.1 mm

Slot Width A1 17.5 mm
0.689 in

Socket Width A2 44.4 mm
1.748 in

Total Height H 120.6 mm
4.748 in

Pitch Height H1 100.8 mm

Height H2 82.6 mm

Total Length L 141.4 mm
5.567 in

Shaft Length L1 88.1 mm
3.469 in

Dimension L2 15.9 mm

Slot Length L3 82.6 mm
3.252 in

Adjustment Screw Bore N 28.6 mm
1.126 in

Opening Width N1 19.00 mm
0.748 in

Opening Height N2 49.2 mm
1.937 in

Inside Ring Width B N/A



Center of Bearing from End S 32.50 mm
1.280 in

Basic Load Ratings



Static Load Rating	4600 lbf 20500 N
--------------------	---------------------

Dynamic Load Rating	8160 lbf 36300 N
---------------------	---------------------



Bearing Number	GY1111KRRB SGT			
Load Ratings - C _r	8150	lbf	36000	N
Load Ratings - C _{0r}	4500	lbf	20000	N
Weight	24.3	lb	11	kg
Bolt Size	M8x1.25			

TIMKEN

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

YTU SGT 1 11/16
Fafnir® Take-Up Units Setscrew Locking

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY