


The Timken Company

4500 Mt Pleasant St. NW



N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number AN 17-W 17, Inch Accessories - Locknut and Lockwasher

- The chart below shows dimensions for locknuts and lockwashers used in the mounting of straight bore bearings on shafts.
- Other dimensions and tolerances related to shaft configurations are also shown.
- Dimensions are presented according to bearing bore size and are applicable to bearings in the various series (e.g., 222 and 223 etc.).



[Specifications](#) | [Threads](#) | [Shaft](#) | [Locknut](#) | [Lockwasher](#)

Specifications

Bearing Bore	85 mm
Threads No. per Inch	12
Locknut	AN 17
Lockwasher	W 17

Threads

Max. Major Diameter	84.84 mm 3.340 in
----------------------------	----------------------

Min. Major Diameter	84.55 mm 3.3288 in
----------------------------	-----------------------

Max. Pitch Diameter	83.46 mm 3.2859 in
----------------------------	-----------------------

Min. Pitch Diameter	83.31 mm 3.2800 in
----------------------------	-----------------------

Minor Diameter	82.24 mm 3.2378 in
-----------------------	-----------------------

Shaft

Relief Diameter A	81.45 mm 3.2065 in
--------------------------	-----------------------

Diameter S-3	80.96 mm 3 3/16 in
---------------------	-----------------------

W¹	4.0 mm 5/32 in
----------------------	-------------------

L²	16.70 mm 0.6563 in
----------------------	-----------------------

H³	3.2 mm 1/8 in
----------------------	------------------

S⁴	9.0 mm 9.5 mm 0.353 in 3/8 in
----------------------	--

M⁵	6.40 mm 1/4 in
----------------------	-------------------

Locknut

C₁	111.90 mm 4 13/32 in
----------------------	-------------------------

D	16.10 mm 0.6350 in
----------	-----------------------

Lockwasher

Q	1.80 mm 0.072 in
----------	---------------------

R	87.0 mm 3.425 in
----------	---------------------

B	117.50 mm 4 5/8 in
----------	-----------------------

¹ Tolerance -0 to + 0.4 mm (-0 to +1/64 in)

² Tolerance -0 to + 0.4 mm (-0 to +1/64 in)

³ Tolerance -0 to + 0.4 mm (-0 to +1/64 in)

⁴ Tolerance -0 to + 0.4 mm (-0 to +1/64 in)

⁵ Tolerance -0 to + 0.4 mm (-0 to +1/64 in)