


The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number 15126 - 15245, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	15000
Cone Part Number	15126
Cup Part Number	15245
Design Units	Imperial
Bearing Weight	0.300 Kg 0.60 lb
Cage Type	Stamped Steel

Dimensions

d - Bore	31.750 mm 1.2500 in
-----------------	------------------------

D - Cup Outer Diameter	61.999 mm 2.4409 in
B - Cone Width	20.638 mm 0.8125 in
C - Cup Width	14.288 mm 0.5625 in
T - Bearing Width	19.050 mm 0.7500 in

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius¹	0.760 mm 0.03 in
r - Cup Backface "To Clear" Radius²	1.27 mm 0.050 in
da - Cone Frontface Backing Diameter	38.10 mm 1.50 in
db - Cone Backface Backing Diameter	38.61 mm 1.52 in
Da - Cup Frontface Backing Diameter	58.42 mm 2.30 in
Db - Cup Backface Backing Diameter	55.12 mm 2.17 in
Ab - Cage-Cone Frontface Clearance	1.8 mm 0.07 in
Aa - Cage-Cone Backface Clearance	0.8 mm 0.03 in
a - Effective Center Location³	-5.8 mm -0.23 in

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁴	15500 N 3490 lbf
---	---------------------

C1 - Dynamic Radial Rating (1 million revolutions)⁵	59900 N 13500 lbf
---	----------------------

C0 - Static Radial Rating	53900 N 12100 lbf
----------------------------------	----------------------

C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁶	9310 N 2090 lbf
---	--------------------

Factors

K - Factor⁷	1.67
-------------------------------	------

e - ISO Factor⁸	0.35
-----------------------------------	------

Y - ISO Factor⁹	1.71
-----------------------------------	------

G1 - Heat Generation Factor (Roller-Raceway)	14.6
---	------

G2 - Heat Generation Factor (Rib-Roller End)	7.58
---	------

Cg - Geometry Factor	0.0606
-----------------------------	--------

¹ These maximum fillet radii will be cleared by the bearing corners.

² These maximum fillet radii will be cleared by the bearing corners.

³ Negative value indicates effective center inside cone backface.

⁴ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.


⁵ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁶ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁷ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e 0.35
ISO Factor - Y 1.71
Bearing Weight 0.6 lb
Number of Rollers Per Row 15
Effective Center Location -0.23 inch

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

15126 - 15245
TS BEARING ASSEMBLY

K Factor 1.67
Dynamic Radial Rating - C90 15500 lbf
Dynamic Thrust Rating - Ca90 9310 lbf
Static Radial Rating - C0 53900 lbf
Dynamic Radial Rating - C1 59900 lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY