


The Timken Company


4500 Mt Pleasant St. NW

N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number YCJT 1 1/4 S, Two-Bolt Flanged Units Setscrew Locking (Includes Industrial and Standard Series)



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#)

Specifications

Bore Size d	1 1/4 in 31.8 mm
Bearing Number	GY1103KRRB3
Dimension E	1.711 in 43.46 mm
Inside Ring Outside Diameter	1.587 in 40.3 mm
Series	Industrial
Weight	2.4 lb 1.09 Kg
Seal Type	Shroud Seal



Dimensions

Total Length H	141.3 mm 5.563 in
Total Height L	79.45 mm 3.128 in
Total Width A	1.177 in 29.9 mm
Bolt Hole Spacing J	116.7 mm 4.594 in
Bolt Hole Size N	11.5 mm 0.453 in
Flange Thickness A1	13.5 mm 0.531 in
Center of Bearing from Housing End A2	20.06 mm 0.790 in
Inside Ring Width B	39.29 mm 1.547 in
Center of Bearing from Bearing End S	20.06 mm 0.790 in

Basic Load Ratings

—

Static Load Rating	2500 lbf 11000 N
Dynamic Load Rating	4900 lbf 21600 N



Bearing Number	GY1103KRRB3			
Load Ratings - C _r	4800	lbf	21600	N
Load Ratings - C _{0r}	2500	lbf	11000	N
Weight		lb		kg
Bolt Size	M6x1			

TIMKEN

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

YCJT 1 1/4 S

Two-Bolt Flanged Units Setscrew Locking
(Includes Industrial and Standard Series)

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY