



Item # 20459434, TUNNELCOTE ROCK DUST Special Hose w/ 10 mm Wide Spiral Reflective Tape 3 in x 400 ft, 100 PSI, Black

APPLICATION: For handling rock dust operations in underground mines. Offered in corrugated or smooth cover. Optional reflective tape available in either style.

CONSTRUCTION TUBE: Black Tufsyn® synthetic rubber (static dissipating / static conductive)

COVER: CORRUGATED (Flextra®): Black Wingprene® synthetic rubber, flame resistant (MSHA) (wrapped impression)

REINFORCEMENT: Spiral-plied synthetic fabric with dual wire helix

TEMPERATURE: -25°F to 200°F (-32°C to 93°C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Soft-cuffed ends standard. Plain ends available upon request.

BRANDING (SPIRAL): Example: Goodyear® TunnelCote™ rock dust flame resistant msha IC-11/14 (embossed)



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Special APP Transfer
Style	Special APP Transfer Hose
Construction Tube	Black Tufsyn® synthetic rubber (static dissipating / static conductive)
Cover	CORRUGATED (Flextra®): Black Wingprene® synthetic rubber, flame resistant (MSHA) (wrapped impression)
Reinforcement	Spiral-plied synthetic fabric with dual wire helix

Color	Black
Min. Temperature	-25 °F -32 °C
Max. Temperature	200 °F 93 °C
Max. Working Pressure	100.0 psi 0.69 MPa
Brand	TUNNELCOTE™ ROCK DUST
Order Code	546-468

Specifications

I.D.	3 in 76.10 mm
Nom. O.D.	3.350 in 85.20 mm
Total Width	3.350 in 85.20 mm
Length	400.000 ft
Bend Radius	8.000 in 203.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	1.210 lb/ft 1.80 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech