



Item # 20013341, NUTRIFLEX Suction & Discharge Hose 2 in x 100 ft, 40 psi, Clear

APPLICATION: Nutriflex™ S&D hose is capable of handling almost every type of dry bulk food material or liquid in gravity flow and vacuum service. Nutriflex conforms to USDA Meat and Poultry, 3-A Sanitary, and FDA Standards and is used for transmission of raw and pasteurized milk and other high water content dairy items.

CONSTRUCTION TUBE: Clear Pliovic® (FDA, 3-A, USDA compliant), NSF-61

COVER: Clear Pliovic (corrugated construction)

REINFORCEMENT: Clear high-density rigid Pliovic® helix

TEMPERATURE: -15 °F to 158 °F (-26 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Dry Bulk Food Material Transfer
Style	Food Hose
Construction Tube	Clear Pliovic® (FDA, 3-A, USDA compliant), NSF-71
Cover	Clear Pliovic (corrugated construction)
Reinforcement	Clear high-density rigid Pliovic® helix
Color	Clear

Min. Temperature	-15 °F -26 °C
Max. Temperature	158 °F 70 °C
Max. Working Pressure	40.0 psi 0.28 MPa
Packaging	Coil
Order Code	586-422
Edited By: Initials and Date	SAS 12/12/12
Brand	NUTRIFLEX™

Specifications

I.D.	2 in 50.80 mm
Nom. O.D.	2.430 in 61.70 mm
Length	100.000 ft
Bend Radius	4.000 in 81.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	0.510 lb/ft 0.76 kg/m

MideastUS@contitech.us
1-800-235-4632
Contitech.us

ContiTech