



## Item # 20019899, EXSTATIC Food Hose 2 in X 100 ft, 150 PSI, Blue

**APPLICATION:** Exstatic® hose is for tank truck and/or in-plant transfer of dry, bulk foodstuffs where there is a potential for electrical static build-up.

**CONSTRUCTION TUBE:** FDA UHMWPE (static dissipating/static conductive) has FDA/USDA compliant materials

**COVER:** Blue SBR(compound)® synthetic rubber (corrugated)/spiral transfer brand (wrapped impression)

**REINFORCEMENT:** Spiral-plyed synthetic fabric with double wire helix

**TEMPERATURE:** -25 °F to 180 °F (-32 °C to 82 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

**BRANDING (SPIRAL):** Example: Continental Contitech Plicord® Exstatic® FDA Dry Material handling 150 psi.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Dry, Bulk Foodstuffs Transfer
Style	Food Hose
Construction Tube	FDA UHMWPE (static dissipating/static conductive) has FDA/USDA compliant materials
Cover	Blue Plioflex® synthetic rubber (corrugated)/spiral transfer brand (wrapped impression)

<b>Reinforcement</b>	Spiral-plyed synthetic fabric with double wire helix
<b>Color</b>	Blue
<b>Min. Temperature</b>	-25 °F -32 °C
<b>Max. Temperature</b>	180 °F 82 °C
<b>Max. Working Pressure</b>	150.0 psi 1.03 MPa
<b>Packaging</b>	Coil
<b>Order Code</b>	549-608
<b>Edited By: Initials and Date</b>	SAS 12/12/12
<b>Brand</b>	EXSTATIC®

## Specifications

<b>I.D.</b>	2 in 50.80 mm
<b>Nom. O.D.</b>	2.500 in 63.50 mm
<b>Length</b>	100.000 ft
<b>Bend Radius</b>	8.000 in 203.00 mm
<b>Vacuum Rating</b>	29.000 inHg 737.00 mmHg
<b>Weight</b>	1.070 lb/ft 1.59 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**