



## Item # 20017558, FLEXWING SUPER Petroleum Transfer Hose 2 1/2 in x 400 ft, 250 psi, Black

**APPLICATION:** A premium high pressure petroleum transfer hose for handling ethanol blends, gasoline, oils and other petroleum products at higher working pressures.

**CONSTRUCTION TUBE:** Special fuel-resistant Black nitrile synthetic rubber RMA Class A (High Oil Resistance)

**COVER:** Black Neoprene synthetic rubber RMA Class A (High Oil Resistance), wrapped finish

**REINFORCEMENT:** Spiral-plied synthetic fabric with wire helix

**TEMPERATURE:** -35 °F to 200 °F (-37 °C to 93 °C)

**COUPLINGS:** Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

**BRANDING:** Example: Continental Contitech Flexwing® Petroleum Hose.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Petrol Transfer
Style	Petrol Transfer Hose
Construction Tube	Special fuel-resistant Black nitrile synthetic rubber RMA Class A (High Oil Resistance)
Cover	Black Neoprene synthetic rubber RMA Class A (High Oil Resistance), wrapped finish
Reinforcement	Spiral-plied synthetic fabric with wire helix

<b>Color</b>	Black
<b>Min. Temperature</b>	-35 °F -37 °C
<b>Max. Temperature</b>	200 °F 93 °C
<b>Max. Working Pressure</b>	300.0 psi 1.72 MPa
<b>Brand</b>	PLICORD® SUPER BLACK FLEXWING®
<b>Order Code</b>	543-117

### Specifications

<b>I.D.</b>	2 1/2 in 63.50 mm
<b>Nom. O.D.</b>	3.110 in 79.00 mm
<b>Total Width</b>	3.110 in 79.00 mm
<b>Length</b>	400.000 ft
<b>Bend Radius</b>	6.000 in 150.00 mm
<b>Vacuum Rating</b>	29.000 inHg 737.00 mmHg
<b>Weight</b>	1.840 lb/ft 2.74 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**