



Item # 20025512, VARIFLEX 300 Air & Multipurpose Hose 1/2 in x 500 ft, 300 PSI, Red

APPLICATION: A good-quality, economical general purpose hose for industrial air service, compressor lines, pneumatic tools, low-pressure spray and many other applications where the need for oil resistance is moderate. Nonconductive, minimum electrical resistance greater than one (1) megohm per inch of length of hose at 1000 V DC. Available in 200 and 300 psi working pressures.

CONSTRUCTION TUBE: Nitrile synthetic rubber, RMA Class A (high oil resistance)

COVER: Red, Blue, or Black Chemivic™ synthetic rubber, RMA Class B (medium oil resistance)

REINFORCEMENT: Spiral synthetic yarn

TEMPERATURE: -20 °F to 190 °F (-29 °C to 88 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: VARIFLEX® Nonconductive 1/2" (12.7 mm) 200 psi WP. Made in USA Continental Contitech.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Air and Multipurpose Transfer
Style	Air and Multipurpose Hose
Reinforcement	Spiral synthetic yarn
Cover	Red Chemivic™ synthetic rubber, RMA Class B (medium oil resistance)
Construction Tube	Nitrile synthetic rubber, RMA Class A (high oil resistance)

Color	Red
Min. Temperature	-20 °F -29 °C
Max. Temperature	190 °F 88 °C
Max. Working Pressure	300.0 psi 2.07 MPa
Packaging	Reel
Brand	VARIFLEX®
Order Code	569-008

Specifications

I.D.	1/2 in 12.70 mm
Nom. O.D.	0.860 in 21.80 mm
Length	500.000 ft
Weight	0.260 lb/ft 0.39 kg/m

MideastUS@contitech.us
 1-800-235-4632
Contitech.us

ContiTech