



## Item # 20025490, VARIFLEX 200 Air & Multipurpose Hose 1/2 in x 500 ft, 200 psi, Red

**APPLICATION:** A good-quality, economical general purpose hose for industrial air service, compressor lines, pneumatic tools, low-pressure spray and many other applications where the need for oil resistance is moderate. Nonconductive, minimum electrical resistance greater than one (1) megohm per inch of length of hose at 1000 V DC. Available in 200 and 300 psi working pressures.

**CONSTRUCTION TUBE:** Nitrile synthetic rubber, RMA Class A (high oil resistance)

**COVER:** Red, Blue, or Black Chemivic™ synthetic rubber, RMA Class B (medium oil resistance)

**REINFORCEMENT:** Spiral synthetic yarn

**TEMPERATURE:** -20 °F to 190 °F (-29 °C to 88 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Example: VARIFLEX® Nonconductive 1/2" (12.7 mm) 200 psi WP. Made in USA Continental Contitech.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Air and Multipurpose Transfer
Style	Air and Multipurpose Hose
Reinforcement	Spiral synthetic yarn
Cover	Red Chemivic™ synthetic rubber, RMA Class B (medium oil resistance)
Construction Tube	Nitrile synthetic rubber, RMA Class A (high oil resistance)

<b>Color</b>	Red
<b>Min. Temperature</b>	-20 °F -29 °C
<b>Max. Temperature</b>	190 °F 88 °C
<b>Max. Working Pressure</b>	200.0 psi 1.38 MPa
<b>Packaging</b>	Reel
<b>Brand</b>	VARIFLEX®
<b>Order Code</b>	569-007

## Specifications

<b>I.D.</b>	1/2 in 12.70 mm
<b>Nom. O.D.</b>	0.840 in 21.30 mm
<b>Length</b>	500.000 ft
<b>Weight</b>	0.210 lb/ft 0.31 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**