



Item # 20024128, MINESPRAY Mining Hose 1 in x 600 ft, 1000 psi, Yellow

APPLICATION: For general underground water spray service in dust control applications. It is also used on continuous mining machinery at the headface and on other mechanical mining machines.

CONSTRUCTION TUBE: Nitrile synthetic rubber RMA Class B (medium oil resistance)

COVER: Yellow Chemivic™ synthetic rubber RMA Class B (medium oil resistance) (Meets flame test requirements of MSHA Schedule 26-Section 18.65), smooth finish

REINFORCEMENT: Braided (1) steel wire

TEMPERATURE: 0 °F to 250 °F (-18 °C to 93 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Continental Contitech 1" Mine Spray 1000 psi WP, Fire-Resistant, USMSHA IC-11/9. Made in USA.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Spray Transfer
Style	Spray Transfer Hose
Construction Tube	Nitrile synthetic rubber RMA Class B (medium oil resistance)
Cover	Yellow Chemivic™ synthetic rubber RMA Class B (medium oil resistance) (Meets flame test requirements of MSHA Schedule 26-Section 18.65), smooth finish
Reinforcement	Braided (1) steel wire

Color	Yellow
Min. Temperature	0 °F 200 °C
Max. Temperature	-18 °F 93 °C
Max. Working Pressure	1000.0 psi 6.90 MPa
Brand	MINE SPRAY
Order Code	539-421

Specifications

I.D.	1 in 25.40 mm
Nom. O.D.	1.450 in 36.80 mm
Length	600.000 ft
Weight	0.630 lb/ft 0.94 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech