



Item # 20046059, PYROFLEX ASPHALT Transfer Hose 2 1/2 in x 400 ft, 150 psi, Black

APPLICATION: For the transfer of high temperature petroleum based materials such as tar, asphalt, and hot oils. It is suitable for suction and discharge service on tank trucks, tank cars or at bulk stations. Heat resistant tube and Flexten reinforcement. (Hot oils only rated to 200 °F).

CONSTRUCTION TUBE: Black Nitrile (special heat resistant) synthetic rubber RMA Class A (High Oil Resistance)

COVER: Black Wingprene® synthetic rubber RMA Class A (High Oil Resistance) with spiral red stripe

REINFORCEMENT: Spiral-plied Flexten® with wire helix

TEMPERATURE: -25 °F to 350 °F (-32 °C to 177 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING (SPIRAL): Example: Continental Contitech Pyroflex Hot Tar and Asphalt II 150 psi.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petrol Transfer
Style	Petrol Transfer Hose
Construction Tube	Black Nitrile (special heat resistant) synthetic rubber RMA Class A (High Oil Resistance)
Cover	Black Wingprene® synthetic rubber RMA Class A (High Oil Resistance) with spiral red stripe

Reinforcement	Spiral-plied Flexten® with wire helix
Color	Black
Min. Temperature	-25 °F 350 °C
Max. Temperature	-32 °F 177 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	PYROFLEX® HOT TAR & ASPHALT II
Packaging	Coiled, Polywrapped
Order Code	543-118

Specifications

I.D.	2 1/2 in 63.50 mm
Nom. O.D.	3.090 in 78.60 mm
Total Width	3.090 in 78.60 mm
Length	400.000 ft
Bend Radius	6.000 in 152.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	1.670 lb/ft 2.49 kg/m

MideastUS@contitech.us
 1-800-235-4632
 Contitech.us

ContiTech