



Item # 20013682, SPIRATHANE PT Transfer Hose 1 1/2 in x 100 ft, 45 psi, Clear/White

APPLICATION: For the transfer of a variety of dry, bulk, and abrasive materials. It is used in applications where static electrical buildup is common. For powders, plastic pellets and granular materials.

CONSTRUCTION TUBE: Polyurethane conforms to FDA standards.

COVER: High molecular weight, clear PVC, corrugated for flexibility.

REINFORCEMENT: High-density, rigid Pliovic® PVC helix with static wire placed between tube and cover.

TEMPERATURE: 0 °F to 158 °F (-18 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Special APP Transfer
Style	Special APP Transfer Hose
Construction Tube	Polyurethane conforms to FDA standards.
Cover	High molecular weight, clear PVC, corrugated for flexibility.
Reinforcement	High-density, rigid Pliovic® PVC helix with static wire placed between tube and cover.
Color	Clear

Min. Temperature	0 °F -18 °C
Max. Temperature	158 °F 70 °C
Brand	SPIRATHANE™ PT
Order Code	586-489

Specifications

I.D.	1 1/2 in 38.10 mm
Nom. O.D.	1.820 in 46.20 mm
Total Width	1.820 in 46.20 mm
Length	100.000 ft
Bend Radius	4.000 in 102.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	0.310 lb/ft 0.46 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech