



Item # 20013500, SPIRAFLEX AGGIE PVC Water S&D Hose 2 in x 100 ft, 79 psi

APPLICATION: A general-purpose water suction hose for use in industrial, agriculture and construction applications.

CONSTRUCTION TUBE: Clear Pliovic®

REINFORCEMENT: High-density white rigid Pliovic helix

TEMPERATURE: 0 °F to 158 °F (-9 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Water Transfer
Style	Water S & D Hose
Construction Tube	Clear Pliovic®
Reinforcement	High-density white rigid Pliovic helix
Color	Clear
Min. Temperature	0 °F -9 °C
Max. Temperature	158 °F 70 °C

Max. Working Pressure	79.0 psi 0.54 MPa
Brand	SPIRAFLEX® AGGIE PVC
Order Code	586-453

Specifications

I.D.	2 in 50.80 mm
Nom. O.D.	2.310 in 58.70 mm
Total Width	2.310 in 58.70 mm
Length	100.000 ft
Bend Radius	8.000 in 203.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	0.580 lb/ft 0.86 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech