



Item # 20021671, REDWING Fuel Oil Dispensing Hose 1 in x 200 ft, 250 PSI, Red

APPLICATION: Redwing® Fuel Oil is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial and industrial service. Redwing Fuel Oil has two textile braids. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

CONSTRUCTION TUBE: Nitrile synthetic rubber (ORS)

COVER: Red Chemivic™ synthetic rubber (smooth finish) (ORS)

REINFORCEMENT: Braided (2) synthetic yarn

TEMPERATURE: -40 °F to 140 °F (-40 °C to 60 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: 1" (25.4 mm) 2 BD Redwing® Fuel Oil Continental Contitech. Made in USA.



Product Specifications | Specifications

Color

Type Oil Transfer Style Redwing Fuel Oil Dispense Hose Construction Tube Nitrile synthetic rubber (ORS) Cover Red Chemivic™ synthetic rubber (smooth finish) (ORS) Reinforcement Braided (2) synthetic yarn

Red

Min. Temperature	-40 °F -40 °C
Max. Temperature	140 °F 60 °C
Max. Working Pressure	250.0 psi 1.72 MPa
Brand	REDWING®
Order Code	532-016

Specifications	
I.D.	1 in 25.40 mm
Nom. O.D.	1.500 in 38.10 mm
Total Width	1.500 in 38.1 mm
Length	200.000 ft
Weight	0.570 lb/ft 0.85 kg/m
Weight	0.6370 lb

MideastUS@contitech.uss 1-800-235-4632 Contitech.us ContiTech