



Item # 20019137, 250 STEAM Hose 3/4 in x 400 ft, 250 PSI, Black

APPLICATION: A rugged construction used for all-around steam service in chemical plants, refineries, shipyards and demanding industrial service. It is recommended for cleaning, thawing, blowout service, steam pumps, hoists and other applications involving steam.

CONSTRUCTION TUBE: Black EPDM(compound)® synthetic rubber

COVER: Black EPDM(compound)® synthetic rubber, also available in red cover with yellow brand for color coding (wrapped impression)

REINFORCEMENT: Spiral-plied steel wire

TEMPERATURE: 0 °F to 406 °F (-18 °C to 208 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING (SPIRAL): Example: Continental Contitech Plicord® Steam 250 psi. Drain after use.



Product Specifications | Specifications

Type Steam Transfer Style Steam Transfer Hose Construction Tube Black Versigard® synthetic rubber Cover Black Versigard® synthetic rubber Reinforcement Spiral-plied steel wire

Color	Black
Min. Temperature	0 °F -18 °C
Max. Temperature	406 °F 208 °C
Max. Working Pressure	250.0 psi 1.72 MPa
Brand	PLICORD® 250 STEAM
Order Code	549-060

Specifications Specification Specificatio		
I.D.	3/4 in 19.10 mm	
Nom. O.D.	1.250 in 31.80 mm	
Total Width	1.250 in 31.8 mm	
Length	400.000 ft	
Weight	0.490 lb/ft 0.73 kg/m	

MideastUS@contitech.uss 1-800-235-4632 Contitech.us

ContiTech