



Item # 20019905, EXSTATIC Food Hose 5 in X 100 ft, 150 PSI, Blue

APPLICATION: Exstatic® hose is for tank truck and/or in-plant transfer of dry, bulk foodstuffs where there is a potential for electrical static build-up.

CONSTRUCTION TUBE: FDA UHMWPE (static dissipating/static conductive) has FDA/USDA compliant materials

COVER: Blue SBR(compound)® synthetic rubber (corrugated)/spiral transfer brand (wrapped impression)

REINFORCEMENT: Spiral-ply synthetic fabric with double wire helix

TEMPERATURE: -25 °F to 180 °F (-32 °C to 82 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

BRANDING (SPIRAL): Example: Continental Contitech Plicord® Exstatic® FDA Dry Material handling 150 psi.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Dry, Bulk Foodstuffs Transfer
Style	Food Hose
Construction Tube	FDA UHMWPE (static dissipating/static conductive) has FDA/USDA compliant materials
Cover	Blue Plioflex® synthetic rubber (corrugated)/spiral transfer brand (wrapped impression)

Reinforcement	Spiral-plyed synthetic fabric with double wire helix
Color	Blue
Min. Temperature	-25 °F -32 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Packaging	Coil
Order Code	549-608
Edited By: Initials and Date	SAS 12/12/12
Brand	EXSTATIC®

Specifications

I.D.	5 in 127.00 mm
Nom. O.D.	5.670 in 144.00 mm
Length	100.000 ft
Bend Radius	20.000 in 508.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	3.690 lb/ft 5.49 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech