



Item # 20013121, SPIRATHANE LD Abrasive / Corrosive Hose 1 1/2 in x 100 ft, 30 psi, Blue

APPLICATION: For dry pneumatic conveying of solid fines where abrasion is present and service conditions are moderate. Excellent for low-pressure blowing applications.

CONSTRUCTION TUBE: Clear Polyurethane, RMA Class B (Medium Oil Resistance)

REINFORCEMENT: High-density rigid white Pliovic® helix

TEMPERATURE: 0 °F to 158 °F (-18 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Abrasive Transfer
Style	Abrasive / Corrosive Hose
Construction Tube	Clear Polyurethane, RMA Class B (Medium Oil Resistance)
Reinforcement	High-density rigid white Pliovic® helix
Color	Clear/White
Min. Temperature	0 °F -18 °C
Max. Temperature	158 °F 70 °C

Max. Working Pressure	30.0 psi 0.21 MPa
Brand	SPIRATHANE™ LD
Order Code	586-406

Specifications

I.D.	1 1/2 in 38.10 mm
Nom. O.D.	1.840 in 46.70 mm
Total Width	1.840 in 46.7 mm
Length	100.000 ft
Bend Radius	2.000 in 51.00 mm
Vacuum Rating	22.000 inHg 559.00 mmHg
Weight	0.250 lb/ft 0.37 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech