



Item # 20013125, SPIRATHANE LD Abrasive / Corrosive Hose 3 in x 100 ft, 20 psi

APPLICATION: For dry pneumatic conveying of solid fines where abrasion is present and service conditions are moderate. Excellent for low-pressure blowing applications.

CONSTRUCTION TUBE: Clear Polyurethane, RMA Class B (Medium Oil Resistance)

REINFORCEMENT: High-density rigid white Pliovic® helix

TEMPERATURE: 0 °F to 158 °F (-18 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Abrasive Transfer
Style	Abrasive / Corrosive Hose
Construction Tube	Clear Polyurethane, RMA Class B (Medium Oil Resistance)
Reinforcement	High-density rigid white Pliovic® helix
Color	Clear/White
Min. Temperature	0 °F -18 °C
Max. Temperature	158 °F 70 °C

Max. Working Pressure	20.0 psi 0.14 MPa
Brand	SPIRATHANE™ LD
Order Code	586-406

Specifications

I.D.	3 in 76.20 mm
Nom. O.D.	3.450 in 87.60 mm
Total Width	3.450 in 87.60 mm
Length	100.000 ft
Bend Radius	4.000 in 102.00 mm
Vacuum Rating	18.000 inHg 457.00 mmHg
Weight	0.600 lb/ft 0.89 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech