



Item # 20016713, PULP & PAPER WASHDOWN Water Hose w/ Optional Integral Tapered Nozzle STIF TN 1 1/4 in x 50 ft, 300 PSI, Black

APPLICATION: Heavy-duty water discharge hose for washdown service in pulp and papermills where kink resistance is of major importance.

CONSTRUCTION TUBE: Black EPDM(compound)® synthetic rubber (also available in white, non-FDA)

COVER: Black EPDM(compound) synthetic rubber

REINFORCEMENT: Spiral-plied synthetic fabric

TEMPERATURE: -25 °F to 200 °F (-32 °C to 93 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Also available with integral tapered nozzle.

BRANDING (SPIRAL): Example: Continental Contitech HD Washdown, 300 psi Max WP.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Water Transfer
Style	Water Suction and Discharge Hose
Construction Tube	Black Versigard® synthetic rubber (also available in white, non-FDA)
Cover	Black Versigard® synthetic rubber
Reinforcement	Spiral-plied synthetic fabric

Color	Black
Min. Temperature	-25 °F -32 °C
Max. Temperature	200 °F 93 °C
Max. Working Pressure	300.0 psi 2.07 MPa
Brand	PULP & PAPER WASHDOWN
Order Code	542-452

Specifications

I.D.	1 1/4 in 31.80 mm
Nom. O.D.	1.880 in 47.80 mm
Length	50.000 ft
Weight	0.810 lb/ft 1.21 kg/m
Orifice Size	5/8 in

MideastUS@contitech.us
 1-800-235-4632
 Contitech.us

ContiTech