



## Item # 20024138, MINESPRAY Mining Hose 1 1/4 in x 400 ft, 1000 psi, Yellow

**APPLICATION:** For general underground water spray service in dust control applications. It is also used on continuous mining machinery at the headface and on other mechanical mining machines.

**CONSTRUCTION TUBE:** Nitrile synthetic rubber RMA Class B (medium oil resistance)

**COVER:** Yellow Chemivic™ synthetic rubber RMA Class B (medium oil resistance) (Meets flame test requirements of MSHA Schedule 26-Section 18.65), smooth finish

**REINFORCEMENT:** Braided (1) steel wire

**TEMPERATURE:** 0 °F to 250 °F (-18 °C to 93 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Example: Continental Contitech 1" Mine Spray 1000 psi WP, Fire-Resistant, USMSHA IC-11/9. Made in USA.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Spray Transfer
Style	Spray Transfer Hose
Construction Tube	Nitrile synthetic rubber RMA Class B (medium oil resistance)
Cover	Yellow Chemivic™ synthetic rubber RMA Class B (medium oil resistance) (Meets flame test requirements of MSHA Schedule 26-Section 18.65), smooth finish
Reinforcement	Braided (1) steel wire

<b>Color</b>	Yellow
<b>Min. Temperature</b>	0 °F 200 °C
<b>Max. Temperature</b>	-18 °F 93 °C
<b>Max. Working Pressure</b>	1000.0 psi 6.90 MPa
<b>Brand</b>	MINE SPRAY
<b>Order Code</b>	539-421

### Specifications

<b>I.D.</b>	1 1/4 in 31.80 mm
<b>Nom. O.D.</b>	1.750 in 44.50 mm
<b>Length</b>	400.000 ft
<b>Weight</b>	0.860 lb/ft 1.28 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**