



Item # 20012502, SPIRAFLEX RED MD Water Discharge Hose 2 1/2 in x 300 ft, 150 psi, Red

APPLICATION: For medium-duty discharge applications in mining, construction, industry, agriculture and marine service. Limited oil and chemical application.

CONSTRUCTION TUBE: Black Pliovic® /Nitrile rubber tube

COVER: Red Pliovic, MSHA 2G-14C/16

REINFORCEMENT: Spiral synthetic yarn, one layer longitudinal synthetic yarn

TEMPERATURE: -10 °F to 150 °F (-23 °C to 66 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Continental Contitech Spiraflex® Red 2" (50.8 mm) 150 psi WP (1.00 MPa), Flame Resistant, USMSHA 2G-14C/16. Made in USA.

Note: Working pressures are rated at 72 °F.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Water Transfer
Style	Water S & D Hose
Construction Tube	Black Pliovic® /Nitrile rubber tube
Cover	Red Pliovic, MSHA 2G-14C/18

Reinforcement	Spiral synthetic yarn, one layer longitudinal synthetic yarn
Color	Red
Min. Temperature	-10 °F -23 °C
Max. Temperature	150 °F 66 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	SPIRAFLEX® RED MEDIUM DUTY
Order Code	537-521

Specifications

I.D.	2 1/2 in 63.50 mm
Nom. O.D.	2.790 in 70.90 mm
Total Width	2.790 in 70.90 mm
Length	300.000 ft
Weight	0.410 lb/ft 0.61 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech